

Technical specification

Total width: 680 mm (600 mm with special wheels)

Total length: 2100 mm (incl. guidance wheel)

Total height when retracted: 1610 mm

Max reach of arm: 4015 mm

Effective working range: up to 6000 mm from center of unit

Weight: 270 kg

Power supply: 24 V DC (2 lead acid batteries at 12 V)

Electric motors: 24 V DC (7 in total)

Ambient temp: 1°C to 55°C (34°F to 131°F)

Storing temp.: Empty of water, -10°C to 75°C (14°F to 167°F)

Control system: Horner PLC

Alarm: Alarm by SMS in the event of operational breakdown

Water supply: From external high-pressure cleaning unit

Nozzle: Rotor jet 0.55

Hose reel: 50 m high pressure hose (operated separately from the robot). Connected to a normal cleaning unit.

Recommended water pressure: 180-210 bar (18-21 MPa)

Recommended water flow: 15-18 l/min

Sound power level1 : 94 dB(A)

Accessories

Charger: see separate specifications supplied with the charger

Markers: design and quantity are dependent on the installation

Nozzle: alternative nozzles may be available depending on the working area

Last
update: 2020/09/11 user_manuals:technical_specification https://wiki.envirologic.se/doku.php/user_manuals:technical_specification?rev=1599818618
03:03

From:
<https://wiki.envirologic.se/> - Envirologic Support Wiki

Permanent link:
https://wiki.envirologic.se/doku.php/user_manuals:technical_specification?rev=1599818618

Last update: 2020/09/11 03:03

